

TDS14000

TELETOUCH telephone interface



Two wire AUTOBUS telephone interface.

Every (DTMF) telephone can be used as an 8 button touch panel (button 1 to 8). In case the TELETOUCH is connected to an external phone line, the user need to enter a password to get access to the system. This only occurs when the number of rings is higher than 0.

The functions and the entrance message are in a user friendly and easy way changeable. This makes the TELETOUCH adaptable to the user needs and wishes.

Application:	Interface to be connected on the AUTOBUS To be used in combination with internal and external telephones.	
Characteristics:	Remote control and activation of 8 domotics functions. Functions are easy adaptable Access with password (if number of rings is higher than 0) Feedback through speech.	
Settings:	Functions:	With PROSOFT Suite
	AUTOBUS address:	through rotary switches Tens + Units
Installation:	DIN rail mounting. To be installed in the direct neighbourhood of the telephone line connection.	
Connections:	AUTOBUS:	AUTOBUS connector set + patch cable supplied with this unit
	Analogue line:	through RJ11 connector
Power Consumption:	Max. 45 mA	
Dimensions:	80 W x 90 H x 60 D (mm) 4.5 units wide	
Gross Weight:	0,320 kg	
IP protection rate:	IP20	

Schematic Drawing:

