

**TDS90460xx**

**Ceiling fixture for SIRIUS**



This premium aluminium ceiling fixture, is supplied in a package containing two pieces. The fixture is available in two colours, white and black: version “WH” and “BL”. The fixture is coated in a textured matte coating and fits perfectly for the TELETASK SIRIUS motion sensor for indoor projects where an ‘on wall/ceiling’ solution is required. This mount contains everything to be used as a GU10 LED fixture for those who are looking for a more homogeneous look of their interior if similar light (LED) housings are used. The holder can rotate 360° and tilt up to 45° for the fine adjustment of the SIRIUS sensor. For even more convenience there is a removable cap that provides more possibilities for easy installation. SIRIUS is not included.

**APPLICATION**

Indoor application to mount the GU10 compatible SIRIUS motion sensor TDS12150xx from TELETASK. Suited for applications where a ‘built in’ solution is not possible or for applications where the motion sensor must be adjusted under an angle of up to 45°.

**General**

Premium aluminium fixture coated in a matte textured coating:

- White: TDS90460WH is RAL9016
- Black: TDS90460BL is RAL9005

**INSTALLATION**

**Ceiling/wall:**

1. Unscrew the circular mounting plate and install it on the desired ceiling position with the supplied 3 screws.
2. Remove the, spring plugged-in rotatable head by pulling it out of the fixture housing.
3. Remove the standard GU10 LED wires and spring (the fixture is only to be used for SIRIUS sensors).
4. Connect the AUTOBUS connector
5. Plug the SIRIUS motion sensor in the rotatable head.
6. Click the rotatable head in place and position.

**Important installation remarks**

- ! Indoor use only
- ! All operations must be performed with power disconnected.
- ! Read the instructions before installation.
- ! Follow the safety standards from the local authorities to be compliant with all regulations.

**CONNECTIONS**

**AUTOBUS**

AUTOBUS connector (supplied with the SIRIUS sensor)

**MAX POWER**

N/A (see SIRIUS data sheet)

**DIMENSIONS**

∅ 85 x 115 H (mm)

**NET | GROSS WEIGHT**

0.520 kg | 0.630 kg

**PACKAGING CONTENT**

2 x TDS90460WH or 2 x TDS90460BL  
3 screws + 3 solid wall plugs

**ENVIRONMENTAL CONDITIONS**

**Storage (with no condensation or icing)**

Temperature: -20°C to +65°C max.  
Relative humidity: 5% to 85% max.

**Operation (with no condensation or icing)**

Temperature: 0°C to +50°C max.  
Relative humidity: 5% to 80% max.

**IP PROTECTION RATE**

IP20

**LIMITED WARRANTY**

1 year

**SCHEMATIC DRAWING**

