



TDS20620V2

DALI-address configuration tool

DALI-address configuration tool for System Integrators.

With this tool you can address any of the individual connected DALI ballasts (address 0 to 63).

Can be used as a tool to configure DALI ballasts connected with the TDS13621 TELETASK DALI Interface.

APPLICATION

Addressing tool for DALI ballasts.

CHARACTERISTICS

General

Software addressing of DALI compatible ballasts.

Supported operating systems

Windows 7 / 8 / 10.

SETTINGS

Configuration

Via PROSOFT Suite 3.6.6 or higher. Address configuration via DALI-SOFT (included with PROSOFT Suite).

INSTALLATION

Unit power supply

Adaptor 24VDC 500mA.

DALI power supply

The device has an integrated bus power supply.

CONNECTION

PC

Micro USB

DALI

Plug-in screw terminal (2 wires)

Power supply

Power jack

DIMENSIONS

67 W x 29 H x 77 D (mm)

NET | PACKED WEIGHT

0,125 kg | 0,170 kg

PACKAGING CONTENT

1x TDS20620V2 tool
1x Power adaptor 24VDC

STORAGE

Temperature

-20°C to +65°C

Relative humidity

15% to 85%

IP PROTECTION RATE

IP21

OPERATING RANGE

Temperature

From 0°C to +50°C

Relative humidity

5% to 80% at 25°C (no humidity/condense)

LIMITED WARRANTY

2 years

SCHEMATIC DRAWING

