

TDS12008xx

Touch panel with 8 buttons



Touch panel with 8 buttons with led indicators, built-in infrared receiver, buzzer and TELETASK IR-link output. The front panel colour can be white or pearl nickel (metal look).

Application:		User interface to be connected on the AUTOBUS
Characteristics:	General	8 buttons (with optional custom engraving of max. 2x7 characters) Infra red receiver.
	Order numbers	TDS12008WH white front TDS12008PN pearl nickel front TDS12008WB white front; B&O IR compatible TDS12008PB pearl nickel front; B&O IR compatible
Settings:	Functions	With PROSOFT Suite
	AUTOBUS address	by rotary switches Tens + Units
	Jumpers	JP1&JP2 baud rate (normal 9600) JP3 terminating resistor (normal out) JP4 night lighting (normal on) JP5 IR-receiver (normal on) JP6 buzzer (normal on)
Installation:		To be mounted in a standard double Belgian wall box, vertically mounted on top of each other.
Connections:	AUTOBUS	By enclosed AUTOBUS connection set
	IR-link	By enclosed AUTOBUS connection set (green wire)
Power Consumption		max. 103 mA
Dimensions:	Front	138 H x 79 W x 3 D (mm)
Gross Weight:		0,320 kg
Schematic Drawing:		

